



Hydraulic Oil Cement Mill, Vertical Raw Mill, Hydraulic System

CJC® Application Study



CUSTOMER

Holcim Philippines Incorporated, Bulacan Plant,
Bulacan Phils.

SYSTEM

Cement mill, vertical raw mill #4,
hydraulic system 1 and 2.
Oil type: ISO VG 68, Tellus-68
Oil volume: 2 x 1,680 Litres

PROBLEM

Holcim Philippines - Bulacan Plant is doing a quarterly machine condition monitoring through oil analysis. On May 15 they found out that the oil in the hydraulic system 1 and 2 on raw mill #4 was heavily contaminated with dust and wear particles. Due to the consequently high costs and profit cuts caused by unplanned maintenance downtimes and shortened oil lifetime Holcim searched for a reliable solution to solve the problems generated by the contaminants in the oil.

SOLUTION

A CJC® Oil-Care system 27/27 with a CJC® Depth Filter insert was installed to reduce the contaminants and wear particles present in the oil.
Filter material: 100% renewable raw material
Filtration degree: 3 µm (micron) up to 1 µm (micron)
Dirt holding capacity: up to 10 kg

RESULT

Within only one month of filtration the oil cleanliness level was reduced from 19/17/14 to 16/14/11 (according to ISO 4406). The installation of the CJC® Oil Care system enabled to attain plant target regarding oil-consumption-ratio (OCR) within shortest time. Furthermore, the mean-time-between-failures (MTBF) was prolonged.

BENEFITS FOR COMPANY AND ENVIRONMENT

The achieved oil cleanliness and extended oil lifetime have a direct, positive impact on the company - less costs (spare parts, maintenance, waste oil, new oil, man power) and increased machine reliability. Only by the avoided oil changes on both hydraulic systems (2x 1,680 litres) Holcim saved approx. 5,455,- EUR and , additionally, 8,736 kg CO₂ (during waste oil incineration would be generated approx. 2.6 kg CO₂ per litre).

COMMENT

Mr. Joel Aycardo, Lubrication Supervisor: "Perfect solution to help our oil-consumption-ratio concerns, now we can save on oil change and can increase our machine reliability."



Holcim Philippines Incorporated, Bulacan Plant, Bulacan Phils.



CJC® Oil-Care System installed at the hydraulic system of the vertical raw mill #4




Sight glass - BEFORE fine filtration



Sight glass - AFTER fine filtration with CJC®

RESULT



	Raw mill #4, system 2		Raw mill #4, system 1	
	BEFORE fine filtration	AFTER 1 month fine filtration with CJC®	BEFORE fine filtration	AFTER 1 month fine filtration with CJC®
Particles > 4 µm	362,600	51,900	263,500	59,600
Particles > 6 µm	101,500	14,500	73,700	16,700
Particles > 14 µm	14,200	2,000	10,300	2,300
ISO Code *)	19/17/14	16/14/11	19/17/14	16/15/12

*) Further information on cleanliness classes are available on request.